

NPD-6001B High PoE midspan

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Supports high-power PoE/PoH and complies to both the IEEE 802.3af and the IEEE 802.3at standards
- ▶ Lightning protection
- ▶ Detects and protects non-standard Ethernet terminals automatically
- ▶ Mounts to a wall, shelf, bench or desktop

60 W Midspan

The 60 W midspan (NPD-6001B) enables remote High Power over Ethernet (High PoE) for various Bosch IP/HD PTZ cameras. Generating a maximum of 60 W, it complies to both the IEEE 802.3af and the IEEE 802.3at standards, while doubling the available power. Rated for indoor installation only, the midspan can be installed indoors and wired to a camera installed outdoors.

The midspan provides surge protection, optimal for installation of outdoor powered devices.

The midspan has a single port and is designed to carry data and power over a standard CAT5e (or better) cable, delivered through all 4 pairs.

Certifications and approvals

Electromagnetic Compatibility (EMC)	Complies with FCC Part 15, ICES-003, and CE regulations, including EN 55032 Class B (emission), EN 55024 (Immunity), and VCCI
Product Safety	Complies with UL/cUL, GS Mark per EN 60950-1

Regulatory Compliance	IEEE 802.3af (PoE), IEEE 802.3at (PoE+, including 2-event), RoHS Compliant, WEEE Compliant, CE
Lightning protection	Meets GR-1089-CORE lightning protection demands EN 61000-4-5 (10/700 µsec, 4kv) Surge protection: IEC 61643-21 ITU-T K.45 International standard

Parts included

Quantity	Component
1	High PoE Midspan 60W, Single port, AC in
1	120 V power cord
1	230 V power cord
1	Quick installation guide

Technical specifications

User Connections

Connectors	Shielded RJ-45 100 Base-TX Ethernet PoE++ EIA 568A and 568B
------------	---

Data

Data transmission	Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet
-------------------	--

Electrical

Input Voltage	100 to 240 VAC, 50/60 Hz
Output Voltage	54-57 VDC (nominal)
Input Current	1.5 A
High Power Over Ethernet (High PoE) Output	Pin Assignment and Polarity: 4 Pair power - Pairs 1/2 (-) and 3/6 (+) - Pairs 7/8 (-) and 4/5 (+) User Port Power: 60 W maximum
Surge protection	Yes

Environmental

Operating Temperature	At 60 W: -10 °C to +40 °C (+14 °F to +104 °F) At 30 W: -10 °C to +50 °C (+14 °F to +122 °F)
Storage Temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Operating Humidity	Maximum 90% relative, non-condensing
Storage Humidity	Maximum 95% relative, non-condensing

Construction

Dimensions (W x H x L)	62 mm x 38 mm x 151 mm (2.44 in. x 1.5 in. x 5.94 in.)
Weight	340 g (0.75 lbs)
Mounting	To wall, shelf, bench or desktop

Miscellaneous

Number of Ports	One (1)
Pass through data rates	10/100/1000 Mbps
Maximum cable length recommended	Not to exceed 100 m (333 ft) between network source and terminal
System Indicators	AC Power (yellow) Channel Power (green)

Ordering information**NPD-6001B High PoE midspan**

High PoE Midspan, 60 W, single port, AC in for AUTODOME 7000 cameras and for MIC7000 cameras without illuminators.

Order number **NPD-6001B**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia