<image><complex-block><complex-block><complex-block>

Features

- ♦ RoHS compliant design
- ♦ One 5.25" and one 3.5" drive bay
- ◆ Two 3.5" internal HDD bays
- Seven expansion slots, compatible with full-size SBC
- ◆ 7 expansion slots, compatible with full-size SBC

Specifications


♦ Construction	Metal with plastic front panel			
♦ SBC Form Factor	Full-size, slot CPU card			
♦ Drive Bays	1 x front-accessible 3.5"			
	1 x 5.25"			
	2 x 3.5" HDD			
♦ Cooling Fans	1 x 8cm			
♦ I/O Openings	1 x LPT, 2 x COM			
♦ Expansion Slots	7 slots			
♦ Indicators	Power, HDD			
♦ Buttons	Power switch, reset			
Operating Temperature	0°C~50°C			
Operation Humidity	10% ~ 90%			
♦ Color	B: Black			
♦ Weight (Net/Gross)	6 kg / 8.4 kg			
Dimensions (DxWxH)	433 mm x 233 mm x 253.7 mm			

Ordering Information

Part No.	Description			
PAC-1700GB-R20/A130A	7-Slot Full-size Compact Chassis, Black, 1 x 8cm fan, with ACE-A130A-R10 (300W ATX model), RoHS			

Dimensions (measurement units: millimeter)





Backplane Options

Model No. SBC Type	PCI	ISA	PCle			PSU Connector	
Model No.	зво туре	FCI	13A	x1	x4	x16	F30 Connector
IP-7SA-RS	PCISA	4	2	0	0	0	AT
PCI-7S-RS	PICMG 1.0	4	3	0	0	0	AT/ATX
¹ PE-7S	PICMG 1.3	3	0	2	0	1	ATX
¹ PE-7S2	PICMG 1.3	1	0	4	0	1	ATX
HPE-7S1	PCI/PICOe	4	0	2	0	0	ATX

¹Only R20 or later version can support PICMG 1.3 backplane

Power Supply Options

Туре	Model No.	Watt
AT	ACE-925AP-U-RS	250W
	ACE-T140A-RS	400W
ATX	ACE-A130A-R10	300W
	ACE-A140A-S-R10	400W

PAC-1700G can support single PS/2 PSU. For more models of IEI PSU, please refer to section 7 or visit www.ieiworld.com.